WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 7228
Rec. June 17 1963
Well No.
Permit No.
Do not fill in

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Owner: Robert Glover Driller: Harold J. Faretto

Address: P.O. Box 562, Reno, Nevada Address: 736 Humboldt St, Reno Lic. No. 2

Location of well: N.E. 1/4 S.W. 1/4 Sec. 34, T. 19 N/S, R. 20 E, in Washoe County

or South of Hidden Valley Golf Links or East of Belli Vista Ranch.

Water will be used for: Prospect Total depth of well: 111'-00"

Size of drilled hole: 6 inch Weight of casing per linear foot: 12.89 Lbs

Thickness of casing: .188 of an inch Temp. of water: ——

Diameter and length of casing: 6 5/8" O.D. Diameter. 5'-11" to 10'-04" lengths
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure:

If nonflowing well give depth of standing water from surface: 104'-00"

If flowing well describe control works:
(Type and size of valve, etc.)

Date of commencement of well: May 24, 1963 Date of completion of well: June 10, 1963

Type of well rig: Speed Star 71 Cable Tool Rig

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	10	10	Sandy soil with a few rocks.
10	64	54	Black soft granite rock & sand.
64	82	18	Rock ledges with sand stratas. (Broken fissures.)
82	90	8	1st. water. Water level 77'-04". Trickle of water. Hardly any water. Rock ledges.
90	93	3	A kind of clay material & sand.
93	100	7	Grano-diorite rock ledges.
100	103	3	A kind of clay material & sand.

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 82 to 90 ft.

Other aquifers: 108-112

First water at 82 feet.

Casing perforated
from ..... to ..... ft.

Size of perforations

(OVER)

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material
108	112	3	2nd water. Water level 104'-00". Grano-diorite rock ledges. Broken fissures. Rocks cave in with sand.

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6 5/8" O.D.	1'-00"	91'-01"	92'-01"	6 5/8" O.D. Black pipe. Welded with 1/4"x3" couplings. Short pattern drive shoe. Well capped.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

A soft granite rock ledges to a harder grano-diorite rock ledges. Sand material sharped edged. A trickle of water very scanty. Muchiron in water. Drilled on a dyke. Owner was cautioned.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Harold J. Faretto
Well Driller

By

License No. 2

Dated June 14, 1963

(Not to be filled in by Driller)

1963 JUN 17 AM 9 58

STATE ENGINEER