7238

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 7099
Rec. Apr. 10 1963
Well No.
Permit No. 18881
Do not fill in

Owner: MAX RIECKE (Estimated) Driller: LOUISE EVANS

Address: P.O. BOX 3312 N. Las Vegas, Nev. [redacted] Carroll N. Las Vegas Lic. No. 117

Location of well: N.W. 1/4 S.E. 1/4 Sec. 19, T. 30 N/S, [redacted] Clark County

T62

or [redacted]

Water will be used for: Domestic Total depth of well: 280 ft.

Size of drilled hole: 200' 8" Weight of casing per linear foot: 12.99 lbs.

Thickness of casing: 3/16 wall Temp. of water:

Diameter and length of casing: 6 5/8" 200 ft.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure:

If nonflowing well give depth of standing water from surface: 60' 7"

If flowing well describe control works:
(Type and size of valve, etc.)

Date of commencement of well: Aug. 14, 1959 Date of completion of well: Aug. 13, 1959

Type of well rig: Keystone

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
			DEEPENED & RUN CASING
80	115	35	red sandy clay
115	200	85	brown sandy clay (water)
200	230	30	brown sticky clay
230	280	50	brown sandy clay (water)

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 230 to 280 ft.

Other aquifers 115 to 200

First water at feet.

Casing perforated

from 74 to 280 ft.

Size of perforations

1/4" wide 6" long

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6 5/8"	74	280	206	

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Louis F Evans
Well Driller

By Louis F. Evans

License No. 117

Dated Sept 2, 19 59

(Not to be filled in by Driller)

1963 APR 10 AM 9 39

STATE ENGINEER