

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 7242  
 Rec. JUNE 24 1963  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*

Owner Robert Mason Driller R. W. Gibson

Address 800 Lockwood Road, Sparks, Nevada Address 465 Sidehill Dr., Sun Valley Lic. No. 359

Location of well: NW 1/4 NW 1/4 Sec. 17, T. 19 N/S, R. 20 E, in Washoe County  
 or \_\_\_\_\_

Water will be used for Domestic Total depth of well 135'

Size of drilled hole 8" Weight of casing per linear foot 17#

Thickness of casing 188 Wall Temp. of water Cold

Diameter and length of casing 8" ID 135'  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 22'

If flowing well describe control works \_\_\_\_\_  
 (Type and size of valve, etc.)

Date of commencement of well 11-27-62 Date of completion of well 12-10-62

Type of well rig 82 Star Well Rig

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, Etc.
0	50		Yellow clay	
50	75		blue clay	Chief aquifer (water-bearing formation)
75	92		red shale & small rock	from <u>92</u> to <u>135</u> ft.
92	135		shale & gravel	Other aquifers _____ <u>small vein at 47'</u>
				First water at <u>47</u> feet.
				Casing perforated from <u>95</u> to <u>135</u> ft.
				Size of perforations <u>1/8"</u>



