

Deepening job below 240

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No.	7284
Rec.	July 15 1963
Well No.	
Permit No.	19699

Do not fill in

Owner Lenord Silvy Driller James M. Davidson

Address Lovlock Nevada Address Lovlock Lic. No. 350

Location of well: NW 1/4 NW 1/4 Sec. 11, T. 27N/3, R. 31E, in Pershing County

or 1/4 mi. No. of Lovlock upper valley
Irrigation

Water will be used for Irrigation Total depth of well 354

Size of drilled hole 14" casing from 240 to 354 Weight of casing per linear foot 10 Ga.

Thickness of casing 10 Ga. Temp. of water

Diameter and length of casing 16" 10Ga. to 240' 14" 10Ga. to 354
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 30

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well July 5 1961 Date of completion of well aug 1 1961

Type of well rig cable tool

LOG OF FORMATIONS				Water-bearing Formation, Casing Perforations, Etc.
From feet	To feet	Thickness feet	Type of material	
240	260	20	blow sand	Chief aquifer (water-bearing formation)
260	324	64	blue clay & gravel	from <u>324</u> to <u>354</u> ft.
324	354	30	water sand and gravel	Other aquifers
				First water at.....feet.
				Casing perforated
				from <u>304</u> to <u>354</u> ft.
				Size of perforations
				factory slots

