

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 7343
 Rec. Aug 22 19 63
 Well No. _____
 Permit No. 21375
Do not fill in
29288

Owner E. A. Becker Driller CASCO 6774-A

Address 5017 Alta Dr., Las Vegas, Nev. Address 1790 E. Plumb Ln., Reno Lic. No. 349

No. I
 Location of well: NE 1/4 SW 1/4 Sec. 3, T 20N/S, R 20E, in Washoe County

Water will be used for Sub-Division Total depth of well 815 ft.

Size of drilled hole 26 inch Weight of casing per linear foot 42.05 lb.

Thickness of casing 0.25 inches Temp. of water 61 degrees

Diameter and length of casing 16" O.D. X 815' total length
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure.....

If nonflowing well give depth of standing water from surface 54 ft.

If flowing well describe control works.....
(Type and size of valve, etc.)

Date of commencement of well 5-4-63 Date of completion of well 8-25-63

Type of well rig Rotary

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, Etc.
0	45	45	Decomposed Granite	54 ft. to T.D. Chief aquifer (water-bearing formation) from to ft. Other aquifers..... First water at <u>54</u> feet. Casing perforated from <u>238.4</u> to <u>812.6</u> ft. Size of perforations <u>machined 1/4" X 3"</u>
45	60	15	D.G./ boulders	
60	80	20	" / " & some blue clay	
80	90	10	Sandy blue clay	
90	100	10	Sand, clay, rocks	
100	105	5	Sand, blue clay	
105	110	5	" " " , some boulders	
110	485	375	Sand/blue clay and gravel (thin) at intervals	
485	490	5	Very fine sand/ blue clay	
490	500	10	Blue clay	
500	665	165	Fine sand/ blue clay	
665	770	105	Blue clay/ med. sand	
770	820	50	Course sand/minor streaks of blue clay	
820	835	15	Crse. sand, clay streaks/ Boulders	
835	840	5	Boulders/clay & sand-hard drilling	
840	848	8	Boulders/sand-minor clay	



