

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 7384  
 Rec. Sept 26 1963  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_

*Do not fill in*

Owner Led Clark Driller James Davidson  
 Address Silver Springs, Nevada Address Bl 69 Fallon Lic. No. 350  
 Location of well: Lot 47 1/4 Sec. 38, T. 11 N, R. 34 E, in Silver Springs County  
 or Lyon Station Flat Bl 69  
 Water will be used for Domestic Total depth of well 280  
 Size of drilled hole 12 Weight of casing per linear foot 19.64  
 Thickness of casing 3/16 Temp. of water cool  
 Diameter and length of casing 8" 280 ft  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_  
 If nonflowing well give depth of standing water from surface 225 ft  
 If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)  
 Date of commencement of well Aug - 27 1963 Date of completion of well Sept 4, 1963  
 Type of well rig Rotary

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
1	10	10	Rock Top soil
10	100	90	Cobbles with sand gravel + some clay
100	130	30	Rock Hard pan
130	140	10	Hard clay
140	247	107	clay
247	250	3	Hard Pan
250	267	17	clay spotted with black sand water
267	280	13	Rock - Black sand

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 267 to 280 ft.

Other aquifers 250 & 267

First water at 250 feet.

Casing perforated from 240 to 280 ft.

Size of perforations

3/8 x 4



