WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 7446
Rec. Oct. 28 1963
Well No.
Permit No.

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Do not fill in

Owner V. Lambertoggi Driller Frank Schuh

Address Tonapah, Nev. Address Austin Nev. Lic. No. 382

Location of well: ¼ ¼ Sec. 9, T. 3N/N/~~S~~ R. 42E, in Esmeralda County

or one-mile south - 3 mils west of Tonapah

Water will be used for Trailer Court Total depth of well 179.

Size of drilled hole 8 in Weight of casing per linear foot 30

Thickness of casing 1/4 Temp. of water

Diameter and length of casing 8-in O.D.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 20 feet from surface.

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well 10-12-63. Date of completion of well 10-24-63.

Type of well rig Cable tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	179	179.	Porphyre

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from ..... to ..... ft.

Other aquifers

100 feet of perforations

First water at 42 feet.
2nd 150

Casing perforated

from 79. to 100 ft.

Size of perforations

1/8 - 6 in long about 30 to a 20 foot joint

(OVER)

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material
0	179	179	Porphyry all the way

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

not test pumped.
There people are to set a
wind mill to pump their water

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Frank [illegible]
Well Driller

By T. D. Hill

License No. 14.

Dated 10-25-, 1963

(Not to be filled in by Driller)

1963 OCT 28 PM 10 54

STATE ENGINEER