

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 7535  
 Rec. Dec. 12. 1963  
 Well No. ....  
 Permit No. ....

Do not fill in.

Owner John Zupanich, Driller F.R. Baxter,  
2688 Yori Avenue, Reno, Nevada. St. R. 1, Box 2490,  
 Address 348 East 8th Ave. Sun Valley, Nev. Address Carson City, Nevada. Lic. No. 322  
 Location of well: 1/4 Sec. 19, T. 20 N/S, R. 20 E, in Washoe County

Water will be used for Home use. Total depth of well 125 ft.

Size of drilled hole 8" Weight of casing per linear foot 9.5 lbs.

Thickness of casing 10 gauge. Temp. of water normal.

Diameter and length of casing 6 inch I.D., length 120 ft.  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure.....

If nonflowing well give depth of standing water from surface 70 ft. (7c)

If flowing well describe control works.....  
(Type and size of valve, etc.)

Date of commencement of well Sept. 14, 1963 Date of completion of well Sept. 19, 1963

Type of well rig Porta-drill. (1500) Rotary.

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	50	50	Sand.
50	100	50	Sand & Clay.
100	120	20	Streaks of Water Sand and gravel.

### Water-bearing Formation, Casing Perforations, etc.

Chief aquifer (water-bearing formation)  
 from 100 ft. to 120 ft.

Other aquifers.....

First water at 100 feet.

Casing perforated  
 from 100' to 120' ft.

Size of perforations  
3/16 inch.

