WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 7589
Rec. Jan 10 1964
Well No.
Permit No.
1890 Do not fill in

Owner: Lawrence & Stegall Ranches, Inc. Driller: Harry Bolton

Address: Montello, Nevada Address: Twin Falls, Idaho Lic. No. 179

Location of well: SE ¼ SW ¼ Sec. 22, T. 44 N/~~S~~, R. 68 E, in Elko County

or

Water will be used for: Stock Total depth of well: 54'

Size of drilled hole: 8" Weight of casing per linear foot: 13 lb.

Thickness of casing: 3/16" Temp. of water:

Diameter and length of casing: 6 5/8" Dia. 55' 4" Long
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure:

If nonflowing well give depth of standing water from surface: 27'

If flowing well describe control works:
(Type and size of valve, etc.)

Date of commencement of well: Sept. 29, 1963 Date of completion of well: Sept 30, 1963

Type of well rig: Churn

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	27'	27'	Clay
27'	38'	11'	Clay & Gravel
38'	52'	14'	Gravel
52'	54'	2'	Clay & Sand

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 27' to 52' ft.

Other aquifers

First water at 27' feet.

Casing perforated

from 32' to 54' ft.

Size of perforations

1/8" x 10"

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6 5/8 OD	From 1' Above Ground	54'	55'	

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

3' draw down @ 30 GPM Baler Test

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Harry Bolton
Well Driller

By.....

License No. 129

Dated October 21, 1963

(Not to be filled in by Driller)