

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

ohh8

Log No. 7744
 Rec. April 3 1967
 Well No.
 Permit No.
Do not fill in.

Rozza PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Owner BUD DONNELLY Driller Enloe Drilling CO.

Address 1330 KOONTZ LANE Address P.O. BOX 519 Carson City Lic. No. 4739

Location of well: N¹/₄ S¹/₄ Sec 29, T. 15. N/8, R. 20. E, in ORMSBY County

Water will be used for Domestic Total depth of well 100

Size of drilled hole 12" Weight of casing per linear foot 13 lbs

Thickness of casing 1.88 Temp. of water.....

Diameter and length of casing 6" 100 ft
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure.....

If nonflowing well give depth of standing water from surface 40-

If flowing well describe control works.....
(Type and size of valve, etc.)

Date of commencement of well March 2 1964 Date of completion of well march 2 1964

Type of well rig Rotary

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	14	14	sandy clay
14	38	24	sandy clay & gravel
38	46	8	clay & some gravel
46	48	2	sand & gravel
48	92	44	clay with traces of gravel
92	94	2	sand
94	100	6	clay

Water-bearing Formation, Casing Perforations, etc.

Chief aquifer (water-bearing formation)
 from 46 to 48 ft.

Other aquifers. ~~92-94~~
92- 94

First water at 26 feet.

Casing perforated
 from 60 to 100 ft.

Size of perforations
1/8 by 2

