

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

7761  
 Log No. \_\_\_\_\_  
 Rec. Apr 23 1964  
 Well No. \_\_\_\_\_  
 Permit No. 21108

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY  
 (Warehouse Enterprises Co.)

Owner RILEY CONSTRUCTION CO. Driller Rodgers cribbs  
 Address 2937 Industrial rd. Address 2710 palomino lane Lic. No. 156  
 Location of well: NE 1/4 SW 1/4 Sec. 8., T.21N/S, R.7E, in CLARK County

Water will be used for Construction Total depth of well 200

Size of drilled hole 10 3/4 Weight of casing per linear foot \_\_\_\_\_

Thickness of casing 1/4 in Temp. of water \_\_\_\_\_

Diameter and length of casing 80 ft 10 3/4 1 wall  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 48

If flowing well describe control works Suck Pump  
(Type and size of valve, etc.)

Date of commencement of well mar. 15 Date of completion of well mar. 21 1963

Type of well rig spudder

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
00	8	8	decomposed lime rock
8	50	42	coarse and cement gravel
50	100	50	brown clay soft sand layers
100	120	20	hard cement gravel
120	200	80	soft sand layers of clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 120 to 125 ft.

Other aquifers 50

First water at 50 feet.

Casing perforated

from 50 to 200 ft.

Size of perforations

1/4 x 6 in