WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 7779
Rec. May 4 1964
Well No.
Permit No.
Do not fill in. 104

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Owner Otis Snodgrass Driller Nevada Pump and Irr. Co. 6648

Address 430 N. Pratt St. Carson City Address 16500 So Vir. Reno Lic. No.

Location of well: ¼ ¼ Sec. 32, T. 16 N/S, R 20 E, in Orms BV County

or Lot 48 Comstock Hills Sub. JPN 08-034-17 4-4-11-01 390 S Sutro Terrace

Water will be used for Domestic Total depth of well 144

Size of drilled hole 12x 12 1/4" Weight of casing per linear foot 13#

Thickness of casing .188 Temp. of water Cold

Diameter and length of casing 6 1/4" x 144'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 25'

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well 4/27/64 Date of completion of well 4/30/64

Type of well rig Rotary

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	15	15	Loam
15	39	19	D.G.
39	144	105	Granite W/ fractures

Water-bearing Formation, Casing Perforations, etc.

Chief aquifer (water-bearing formation)

from 50 to 144 ft.

Other aquifers

First water at 50 feet.

Casing perforated

from 124 to 143 ft.

Size of perforations

1/8 x 8" Burned

(OVER)

919

LOG OF FORMATIONS—Continued

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	REMARKS—Seals, Grouting, etc.
6 1/4"	0	144	144	Grout seal from 28' to surface mixture of bentonite and cement

GENERAL INFORMATION—Pumping Test, Quality of Water, etc.

Well was blown with 1000CFM compressor and produced approx. 20 GPM

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed [illegible] Pump & Supply Co.
Well Driller

By [illegible]

License No. 439

Dated 5-1-, 196[illegible]

(Not to be filled in by Driller)