Log No. 7796
Rec. May 8 1964
Well No.
Permit No.
Do not fill in.

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Owner: Lindesmith Driller: A & B Contractors

Address: Farretto Lane, Reno Address: Sun Valley, Nevada Lic. No. 287

Location of well: SW ¼ SE ¼ Sec. 2, T. 18 N/S, R 19 E, in Washoe County

or

Water will be used for: domestic Total depth of well: 378'

Size of drilled hole: 6-5/8" Weight of casing per linear foot: 13 lbs.

Thickness of casing: 188 ga. Temp. of water: cold

Diameter and length of casing: 6-5/8 X 196'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface: 40'

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well: 12-18-63 Date of completion of well: 1-20-64

Type of well rig: cable tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	50	50	clay & rock
50	165	115	red volcanic rock
165	265	100	red andicite
265	290	25	hard red andicite
290	348	58	soft red andicite
348	378	30	cubed andicite

(OVER)

Water-bearing Formation, Casing Perforations, etc.

Chief aquifer (water-bearing formation)

from 148 to 165 ft.

Other aquifers

260 to 290

348

First water at 65 feet.

Casing perforated

from 156 to 196 ft.

Size of perforations

1/8 X 6"

LOG OF FORMATIONS—Continued

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	REMARKS—Seals, Grouting, etc.
6-5/8	1	0	196	188 ga; welded joints; drive shoe.

GENERAL INFORMATION—Pumping Test, Quality of Water, etc.

40 GPM; 5' DD; bail test.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed A & B Contractors
Well Driller

By Millard Artlip

License No. 287

Dated May 6, 1964

(Not to be filled in by Driller)