

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

✓ Log No. 7799
 Rec. Mo 8 1964
 Well No.
 Permit No.

Do not fill in.

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Owner John Breckenridge Driller A. & B. Contractors

Address Topaz Lake, Nevada Address Sun Valley, Nevada Lic. No. 287

Location of well NE 1/4 NW 1/4 Sec. 31, T. 10 N/8, R. 22 E, in Douglas County

or

Water will be used for domestic Total depth of well 150'

Size of drilled hole 6" Weight of casing per linear foot 12 Lbs.

Thickness of casing 188 ga. Temp. of water cold

Diameter and length of casing 6" X 150'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 15'

If flowing well describe control works

(Type and size of valve, etc.)

Date of commencement of well 10-1-63 Date of completion of well 10-7-63

Type of well rig cable tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	18	188	clay & rock
18	145	127	clay & gravel
145	150	5	water bearing sand

Water-bearing Formation, Casing Perforations, etc.

Chief aquifer (water-bearing formation)
 from 145 to 150 ft.

Other aquifers

First water at 145 feet.

Casing perforated
 from 110 to 150 ft.

Size of perforations
1/8 X 6"

