WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 7800
Rec. May 8 19 64
Well No.
Permit No.
Do not fill in

Owner: Ellen Brunzell
Driller: A & B Contractors
Address: Wadsworth, Nevada
Address: Sun Valley, Nevada
Lic. No. 287

Location of well: S.E. 1/4 N.W. 1/4 Sec. 3, T. 20 N/S, R. 24 E, in Washoe County

or

Water will be used for: domestic
Total depth of well: 82'

Size of drilled hole: 6"
Weight of casing per linear foot: 13 lbs

Thickness of casing: 188 gauge
Temp. of water: cold

Diameter and length of casing: 6-5/8" X 81'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure:

If nonflowing well give depth of standing water from surface: 32'

If flowing well describe control works:
(Type and size of valve, etc.)

Date of commencement of well: March 8-63
Date of completion of well: March 11-63

Type of well rig: cable tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	2	2	sandy loam
2	40	38	sand, clay & boulders
40	55	15	sandy clay
55	80	25	heavy sand
80	82	2	sandy clay

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 55 to 80 ft.

Other aquifers:

First water at 55 feet.

Casing perforated
from 60 to 75 ft.

Size of perforations: 1/8 X 6"

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6-5/8	1	0	81	188 gauge welded joi nts; 1 scab Gopher drive shoe

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

25 Gal. per min.; 10 ft. draw down; bail test

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed A J B Contractors
Well Driller

By M. Curtis

License No. 6538

Dated Mar 11, 1963

(Not to be filled in by Driller)

1963 MAR 8 PM 2 49