WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 7818
Rec. May 8 1964
Well No.
Permit No.
Do not fill in.

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Owner: Ainsworth & Martin Driller: A & B Contractors

Address: Pyramid & Wedekind Rd, Sparks, Nev. Address: Sun Valley, Nev. Lic. No. 287

Location of well: SW ¼ SW ¼ Sec. 28, T. 20 N/S, R. 20 E, in Washoe County

or

Water will be used for: domestic Total depth of well: 206'

Size of drilled hole: 6-5/8" Weight of casing per linear foot: 13#

Thickness of casing: 188 ga. Temp. of water: cold

Diameter and length of casing: 6-5/8" X 206'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well: 7-6-63 Date of completion of well: 7-22-63

Type of well rig: cable tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	165	165	brown rock
165	175	10	grey mud
175	200	25	grey shale
200	206	6	andicite rock

(OVER)

Water-bearing Formation, Casing Perforations, etc.

Chief aquifer (water-bearing formation)
from 175 to 200 ft.

Other aquifers

First water at 165 feet.

Casing perforated
from 160 to 206 ft.

Size of perforations
1/8 X 6"

919

LOG OF FORMATIONS—Continued

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	REMARKS—Seals, Grouting, etc.
6-5/8"	1	0	206	188 ga; welded joints; drive shoe

GENERAL INFORMATION—Pumping Test, Quality of Water, etc.

10 GPM; 80' DD; bail test

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed A & B Contractors
Well Driller

By M. Arthur

License No. 287

Dated April 16, 1964

(Not to be filled in by Driller)