WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 7820
Rec. May 8 1964
Well No.
Permit No.
Do not fill in.

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Owner Shane Metals, Inc. Driller A & B Contractors

Address Sparks, Nev. Address Sun Valley, Nev. Lic. No. 287

Location of well: NE¼NW¼ Sec. 8, T. 19 N/S, R. 20 E, in Washoe County

or

Water will be used for fire protection Total depth of well 70'

Size of drilled hole 6-5/8" Weight of casing per linear foot 13#

Thickness of casing 188 ga. Temp. of water cold

Diameter and length of casing 6-5/8" X 70'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 8'

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well 3-4-64 Date of completion of well 3-10-64

Type of well rig cable tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	8	8	Top soil
8	35	27	sandy clay
35	45	10	sand & gravel
45	65	20	sandy clay
65	70	5	gravel

(OVER)

Water-bearing Formation, Casing Perforations, etc.

Chief aquifer (water-bearing formation)

from 65 to 70 ft.

Other aquifers

First water at 8 feet.

Casing perforated

from 60 to 70 ft.

Size of perforations

1/8 X 6"

919

LOG OF FORMATIONS—Continued

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	REMARKS—Seals, Grouting, etc.
6-5/8"	1	0	70	188 ga; welded joints; drive shoe

GENERAL INFORMATION—Pumping Test, Quality of Water, etc.

40 GPM; no DD; bail test

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed A J B Contractors
Well Driller

By M. Artlip

License No. 287

Dated April 16, 1964

(Not to be filled in by Driller)