WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 7851
Rec. May 28 1964
Well No.
Permit No.
Do not fill in.

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Owner Robert Kobman Driller W. E. Blain

Address 106 East B St Sparks Address Box 255 Carson City Lic. No. 301

Location of well: ¼ ¼ Sec. 6, T. 16 N/S, R 22 E, in Washoe County

or Lot 9 Block P Washoe Valley Farms Corner Pershing Lane & Esmeralda Drive

Water will be used for Domestic Total depth of well 83 ft

Size of drilled hole 10" to 48 ft Weight of casing per linear foot 9.7 lbs

Thickness of casing 10 gage Temp. of water Cold

Diameter and length of casing 6" x 84 ft (4 ft lengths)
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 46 ft

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well 4-29-64 Date of completion of well 4-30-64

Type of well rig Cable Tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	4	4	Soil
4	22	18	Sandy clay
22	24	2	Sand
24	40	16	Sandy clay
40	61	21	Sand
61	65	4	Clay
65	82	17	Sand
82	83	1	Clay

Water-bearing Formation, Casing Perforations, etc.

Chief aquifer (water-bearing formation)

from 65 to 82 ft.

Other aquifers 48 61

First water at 48 feet.

Casing perforated

from 64 to 84 ft.

Size of perforations

3 X 3/32

(OVER)

919

LOG OF FORMATIONS—Continued

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	REMARKS—Seals, Grouting, etc.
6"	0	53	54	Sealed to 45 ft with native clay

GENERAL INFORMATION—Pumping Test, Quality of Water, etc.

Test by bailing - 32 G.P.M.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed W. E. Blair
Well Driller

By Florence Blair

License No. 361

Dated 5-25, 1964

(Not to be filled in by Driller)