Log No. 7269
Rec. June 22 1964
Well No.
Permit No.
Do not fill in.
6648

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Owner Don Bergeron Driller Nevada Pump and Irr. Co

Address Star Route 1 Box 690 Carson City Address 15500 So. Virg Reno Lic. No.

Location of well: SW ¼ SW ¼ Sec. 23, T. 19 N/S, R. 20 E, in Washoe County

or

Water will be used for Domestic Total depth of well 100'

Size of drilled hole 12 1/4" Weight of casing per linear foot 12.88

Thickness of casing .188 Temp. of water ~~Cold~~ Cold

Diameter and length of casing 6 1/4 x 100'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 1'

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well 6/4/64 Date of completion of well 6/4/64

Type of well rig Rotary

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	15	15	Sand
15	75	60	Sandy Clay
75	100	25	Coarse Sand w/ water

(OVER)

Water-bearing Formation, Casing Perforations, etc.

Chief aquifer (water-bearing formation)

from 75 to 100 ft.

Other aquifers

First water at 62 feet.

Casing perforated

from 80 to 98 ft.

Size of perforations

1/8" x 8" Burned

919

LOG OF FORMATIONS—Continued

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	REMARKS—Seals, Grouting, etc.
6 1/4	0	100	100	Well was blown with air and produced approx. 30 GPM Grout seal bentonite and cement from 0 to 35 '

GENERAL INFORMATION—Pumping Test, Quality of Water, etc.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Nevada Pump and Irr. Co
Well Driller

By E J Finch

License No. 439

Dated 6-13, 1964

(Not to be filled in by Driller)