MF 50-[illegible]-05

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 7905
Rec. June 12 1964
Well No.
Permit No.

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Do not fill in

Owner Robert Reynolds Driller Pete Anderson

Address 1120 Belden Way Reno, Nev Address 604 E 4th St Reno Nev Lic. No. 307

Location of well: ¼ ¼ Sec. 31, T. 17 N/S, R. 20 E, in Washoe County

or Sub 3 Block J. Lot 6 New Washoe City

Water will be used for Domestic Total depth of well 60'

Size of drilled hole 6" Weight of casing per linear foot 13 lbs

Thickness of casing 3/16 or 1.88 Temp. of water Cool

Diameter and length of casing 6" 58'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 25'

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well May 15-64 Date of completion of well May 18, 64

Type of well rig Cable Tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	30'	30'	Loose Sand
30	45	15'	Blue Sand
45	60	15'	Blue Sand & Gravel

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 45 to 60 ft.

Other aquifers 30' 45'

First water at 25' feet.

Casing perforated
from 48' to 58' ft.

Size of perforations
1/8 x 4" Torch Cut

(OVER)

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6"	0	58'	58'	All joints electric welded + clay returned to outside of casing

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Well bailed for one hour complete draw down with 8 G.P.M. returning to well

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed [signature]
Well Driller

By

License No. 307

Dated ~~May 27~~ June 10, 1964

(Not to be filled in by Driller)