WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 7923
Rec. June 18 1964
Well No.
Permit No.
Do not fill in.

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Owner: [illegible] Liddleton Driller: Meyer Drilling Co. Carson

Address: 1163 W. 5th St. Carson Address: 505 Hot Springs Rd. Lic. No. [illegible]

Location of well: [illegible] ¼ [illegible] ¼ Sec. 31, T. 15 N/S, R. 20 E, in Ormsby County

Approx.

or: Bar Stewart- Roventini Way & Oak St.

Water will be used for: Domestic Total depth of well: 145 ft.

Size of drilled hole: 6 Inch Weight of casing per linear foot: 15 lb.

Thickness of casing: .188 Wall Temp. of water: Cool

Diameter and length of casing: 6" x 145'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure: Not Flowing

If nonflowing well give depth of standing water from surface: 80 ft.

If flowing well describe control works: Not Flowing
(Type and size of valve, etc.)

Date of commencement of well: 4-1-64 Date of completion of well: 4-11-64

Type of well rig: 72 Star, Cable Tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	145	145	Sand all the way

Water-bearing Formation, Casing Perforations, etc.

Chief aquifer (water-bearing formation)

from 90 to 145 ft.

Other aquifers

First water at 90 feet.

Casing perforated

from 90 to 145 ft.

Size of perforations

1/4" X 6" Torch

(OVER)

919

LOG OF FORMATIONS—Continued

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	REMARKS—Seals, Grouting, etc.
6 5/8 OD	0	145	145'	

GENERAL INFORMATION—Pumping Test, Quality of Water, etc.

12 GPM @ 90' [illegible]

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed [illegible] Drilling Company
Well Driller

By

License No. 200

Dated June 16, 1984, 19

(Not to be filled in by Driller)