LOG OF FORMATIONS—Continued

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	REMARKS—Seals, Grouting, etc.
6" OD	0	160	160	18" hole drilled and grouted to 40'

GENERAL INFORMATION—Pumping Test, Quality of Water, etc.

Standing water level	41' 5"
g.p.m. pumped	3 g.p.m.
No draw down check probe hung up	
Pumping time	4 hours

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Hatch Drilling Co.
Well Driller

By [signature]

License No. 352

Dated 12/28, 19 63

(Not to be filled in by Driller)

1964 JUL 17 PM 2 38

STATE ENGINEER
OFFICE

Permit No: 19796

Log No. 7984
Rec. July 17 1964
Well No.
Permit No. ~~19796~~
Do not fill in.

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

11 CMAA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Owner North American Aviation, Inc. Driller Hatch Drilling Co.

Address P. O. Box 4800, Reno, Nevada Address 1700 Holcomb Lane Lic. No. 352

Location of well: NE ¼ SW ¼ Sec. 11, T. 22 N/S, R21 E, in Washoe County

or APN 077-110-14 Palomino V. Unit 1 11-2-1-10 AKA well T-5
Whiskey Springs Road

Water will be used for ~~xxxxxxxxxxxxxxxxxxxxxxxxxxxx~~ Total depth of well 600 feet

Size of drilled hole 5 5/8 Weight of casing per linear foot 4.42 lbs.

Thickness of casing 12 gage Temp. of water cold

Diameter and length of casing 4" OD 160 feet
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 41 ft. 5 inches

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well 10/4/63 Date of completion of well 10/9/63

Type of well rig Rotary

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	35	35	Fractured rock
35	120	85	Peagravel layers rock
120	180	60	Course sand w/gravel
180	263	83	Gravel, sand w/clay streaks
263	276	13	Hard rock
276	338	64	Clay and gravel
338	520	182	Fine sand w/clay & gravel
520	600	80	Sandy clay w/some gravel

REMARKS: This well drilled in a different location than advertised exact location as described above

(OVER)

Water-bearing Formation, Casing Perforations, etc.

Chief aquifer (water-bearing formation)

from 120 to 180 ft.

Other aquifers

First water at feet.

Casing perforated

from 140 to 160 ft.

Size of perforations

1/8" x 8" torch cut

919