


# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY



8205  
 Log No. ~~8069~~  
 Rec. Nov. 13 1964  
 Well No. \_\_\_\_\_  
 Permit No. 25767  
 Do not fill in.

Owner Elizabeth Zeinndt Driller Reno Pump and Supply  
 Address 1652 White Creek Lane - Reno, Nev. Address 7466 So. Virginia - Reno Lic. No. 285  
 Location of well: N 1/4 N 1/4 Sec 29, T. 18 N/S, R. 20 E, in Washoe County  
 or \_\_\_\_\_  
 Water will be used for Domestic Total depth of well 265'  
 Size of drilled hole 6" x 265' Weight of casing per linear foot \_\_\_\_\_  
 Thickness of casing 6" x 219" Wall Casing Temp. of water Warm  
 Diameter and length of casing 6" x 131'  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_  
 If nonflowing well give depth of standing water from surface 50'  
 If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)  
 Date of commencement of well December 12, 1963 Date of completion of well January 14, 1964  
 Type of well rig Cable Tool

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, etc.
0'	1'	1'	Top Soil	
1'	12'	11'	Clay, Boulders and Gravel	Chief aquifer (water-bearing formation)
12'	29'	17'	Clay, Sand and Gravel with Boulders	from <u>60'</u> to <u>78'</u> ft.
29'	31'	2'	Clay, Sand and Gravel	Other aquifers _____
31'	32'	1'	Decomposed Granite	
32'	36'	4'	Granite Sand	
36'	45'	9'	Sand, Gravel, Boulders and Clay	
45'	60'	15'	Clay, Gravel and Boulders	
60'	67'	7'	Boulders and Gravel W/B	
67'	78'	11'	Sand, Clay, Gravel and Boulders W/B	
78'	130'	52'	Clay, Sand and Small Gravel Turning Hard	First water at <u>60'</u> feet.
130'	175'	45'	Pinkish Clay and Small Gravel Getting Hot	Casing perforated
175'	235'	60'	Blue Clay and Gravel	from <u>60'</u> to <u>78'</u> ft.
235'	250'	15'	Gray Brown Clay and Gravel	
250'	265'	15'	Blue-Gray Clay and Gravel	Size of perforations _____
				<u>Mills Knife</u>

**LOG OF FORMATIONS—Continued**

From feet	To feet	Thickness	Type of material

**CASING RECORD**

Diam. casing	From feet	To feet	Length	REMARKS—Seals, Grouting, etc.
6"	0	131	131'	Well was grouted to approx. 45' with 5 sack mix neat cement.

**GENERAL INFORMATION—Pumping Test, Quality of Water, etc.**

Well was pumped with a 1 HP submersible pump for 2 1/2 hours at approx. 18 gpm.

---



---



---

**WELL DRILLER'S STATEMENT**

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed *Joe A. Parker*  
Well Driller

By.....

License No. 3113

Dated 10/29/64

**(Not to be filled in by Driller)**

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

1964 NOV 13 PM 3 08

STATE ENGINEER