

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 206 2070
 Rec. Nov. 13 1964
 Well No.
 Permit No.

Do not fill in.

Owner Devere Barker Driller Reno Pump and Supply

Address 2114 Bondorosa Drive - Sparks, Nev. Address 7468 So. Virginia - Reno Lic. No. 235

Location of well: NE 1/4 NW 1/4 Sec. 6, T. 19. N/S, R. 20. E, in Washoe County

Water will be used for Domestic Total depth of well 70'

Size of drilled hole 6" Weight of casing per linear foot

Thickness of casing .100 Temp. of water Cold

Diameter and length of casing 6" x 70'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 1.7'

If flowing well describe control works

(Type and size of valve, etc.)

Date of commencement of well March 14, 1963 Date of completion of well March 21, 1963

Type of well rig Cable Tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0'	6'	6'	Top Soil and Clay
6'	21'	15'	Clay, Sand and Large Gravel
21'	30'	9'	Gravel and Sandy Clay W/B
30'	32'	2'	Sand and Silt
32'	65'	33'	Sand, Gravel and Clay
65'	70'	5'	Decomposed Brown Rock W/B

Water-bearing Formation, Casing Perforations, etc.

Chief aquifer (water-bearing formation)
 from 55' to 70' ft.

Other aquifers See log.

First water at 21 feet.

Casing perforated
 from 51' to 60' ft.

Size of perforations
1/2" x 3" Torch cut

