

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

210  
 Log No. 8077  
 Rec. Nov. 13, 1964  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
 Do not fill in.

Owner Clarence Smith Driller Reno Pump and Supply

Address Route 1 Box 214 Carson City, Nev. Address 7468 So. Virginia - Reno Lic. No. 285

Location of well: SW 1/4 NE 1/4 Sec. 23., T. 15. N/S, R. 20. E, in Ormsby County  
 or \_\_\_\_\_

Water will be used for Domestic Total depth of well 84'

Size of drilled hole 6" x 84' Weight of casing per linear foot \_\_\_\_\_

Thickness of casing .100 A53 Temp. of water Cold

Diameter and length of casing 6" x 84'  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 60'

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well June 12, 1964 Date of completion of well June 16, 1964

Type of well rig Cable Tool

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0'	28'	28'	Sandy Clay
28'	60'	32'	Clay and Sand
60'	84'	24'	Sand w/B

### Water-bearing Formation, Casing Perforations, etc.

Chief aquifer (water-bearing formation)

from 60' to 84' ft.

Other aquifers \_\_\_\_\_

First water at 60' feet.

Casing perforated

from 56' to 80' ft.

Size of perforations

3/32" x 3" Saw cut

