


# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY



Log No. 8277  
 Rec. Jan 5 1966  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*

Owner J.C. Wagner Driller A. & B. Contractors  
 Address Fernley Nevada Address Sun Valley Lic. No. 287

Location of well: S<sup>1</sup>/<sub>2</sub> 1/4 NE 1/4 Sec. 20, T20 N/S, R24 E, in Lyon County  
 or Well #2 Lot 5 Wagner Sub.

Water will be used for Domestic Total depth of well 100'

Size of drilled hole 6 5/8 Weight of casing per linear foot 13#

Thickness of casing 188 Well Temp. of water Cold

Diameter and length of casing 6 5/8 x 90'  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 62'

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well Dec. 6 1964 Date of completion of well Dec. 14 1964

Type of well rig Cable Tool

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	10	10	Sandy Top Soil
10	40	30	Sandy Clay
40	65	25	Tight Sandy Clay
65	100	35	Sand & Clay in Layers

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 65 to 100 ft.

Other aquifers \_\_\_\_\_

First water at 65 feet.

Casing perforated

from 70 to 90 ft.

Size of perforations

1/8 x 6"







