

CLEVELAND WELL  
**WELL LOG AND REPORT TO THE STATE ENGINEER  
 OF NEVADA**

Log No. 8327  
 Rec. Jan 25 1965  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
 Do not fill in: 179

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Owner Bureau of Land Management Driller Lee Bennett  
 Address Ely, Nevada Address 470 High St., Ely, Nev. Lic. No. 416  
 Location of well: 1/4 NE 1/4 Sec 26, T. 6 N., R. 66 E. in White Pine County  
 or NE<sup>4</sup>, Section 26, T. 6 N., R. 66 E. - Spring Valley  
 Water will be used for Stock Total depth of well 260 ft.  
 Size of drilled hole 6" Weight of casing per linear foot 10 lb.  
 Thickness of casing 1/4 Temp. of water Warm  
 Diameter and length of casing 6" ID 260'  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_  
 If nonflowing well give depth of standing water from surface 220'  
 If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)  
 Date of commencement of well December 2, 1964 Date of completion of well December 10, 1964  
 Type of well rig 24-L Bucyrus Erie Cable tool

**LOG OF FORMATIONS**

From feet	To feet	Thickness feet	Type of material
0	140'	140'	Boulders in sand
140'	230'	90'	Sand
230'	260'	30'	Sand and gravel

**Water-bearing Formation, Casing Perforations, etc.**

Chief aquifer (water-bearing formation)  
 from 230' to 260 ft.  
 Other aquifers \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 First water at 230 feet.  
 Casing perforated  
 from 230 to 260 ft.  
 Size of perforations  
1/8 x 6" 5 to the  
round every 2'

