

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA



Log No. 8409  
 Rec. Mar 26 1965  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Do not fill in.

Owner Swift Builders Driller H.A.H. Drilling  
 Address Gardnerville, Nevada Address 580 Casazza Dr. Lic. No. 7124  
 Location of well:  $\frac{1}{4}$   $\frac{1}{4}$  Sec. 5, T. 12 N/S, R. 20 E, in Douglasa County  
 or Gardnerville Ranchos  
 Water will be used for Domestic Total depth of well 100'  
 Size of drilled hole 6" Weight of casing per linear foot \_\_\_\_\_  
 Thickness of casing \_\_\_\_\_ Temp. of water Cold  
 Diameter and length of casing \_\_\_\_\_  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_  
 If nonflowing well give depth of standing water from surface \_\_\_\_\_  
 If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)  
 Date of commencement of well February 23 Date of completion of well March 8  
 Type of well rig Cable Tool

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	20	20	Boulders, clay
20	35	15	Boulders, clay
35	50	15	Boulders, clay
50	70	20	Sand Gravel (course)
70	100	30	Sand Course Gravel; 70-100 was water bearing gravel

#### Water-bearing Formation, Casing Perforations, etc.

Chief aquifer (water-bearing formation)  
 from 70 to 100 ft.  
 Other aquifers None  
 First water at 70 feet.  
 Casing perforated  
 from 80 to 100 ft.  
 Size of perforations  
3" X 3/8"



