Log No. 8422
Rec. April 8 1965
Well No.
Permit No.
Do not fill in.

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Owner: Roger Hardin Driller: Pat Anderson

Address: Moapa City, Nev. Address: Box 85 Stanfield Ariz. Lic. No. 307

Location of well: ¼ ¼ Sec. 6, T. 17 N/S, R. 20 E, in Moapa County

or Moapa Valley Farms

Water will be used for: Domestic Total depth of well: 85'

Size of drilled hole: 6" Weight of casing per linear foot: 13 lbs

Thickness of casing: 3/16" or .188 Temp. of water: Cold

Diameter and length of casing: 6" 85'

(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface: 1 ft + 6"

If flowing well describe control works

(Type and size of valve, etc.)

Date of commencement of well: March 16-65 Date of completion of well: March 15-65

Type of well rig: Cable tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	18	18	Loose sand
18	30	12	Sand some gravel
30	45	15	Blue sand + silt
45	60	15	Blue clay
60	70	10	Sand + silt
70	85	15	Sand gravel

(OVER)

Water-bearing Formation, Casing Perforations, etc.

Chief aquifer (water-bearing formation)

from 72 to 85 ft.

Other aquifers: 18' - 30'
60' - 70'

First water at 8 feet.

Casing perforated

from 72 to 85 ft.

Size of perforations

¼ x 2

919

LOG OF FORMATIONS—Continued

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	REMARKS—Seals, Grouting, etc.
6	0	85	85	All joints [illegible] & clay [illegible] to outside of casing

GENERAL INFORMATION—Pumping Test, Quality of Water, etc.

Bailed for 20 minutes. 20' draw down at 30 G.P.M.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed [illegible]
Well Driller

By.....

License No. 307

Dated April 6, 1965

(Not to be filled in by Driller)