WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 8501
Rec. May 24 1965
Well No. [illegible]
Permit No.
Do not fill in

Owner: [illegible] Pacific Power Company Driller: C.M. [illegible] of Layne Texas Co.

Address: Reno Nevada Address: Po Box 9469 Houston Tex Lic. No. 5573

Location of well: [illegible] ¼ ¼ Sec. 34, T. 21 N/S, R. [illegible] E, in Washoe County

or

Water will be used for: Test Hole only Total depth of well: [illegible]

Size of drilled hole: 9 7/8 Weight of casing per linear foot

Thickness of casing Temp. of water

Diameter and length of casing
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well: 4-6-64 Date of completion of well: 4-10-64

Type of well rig: Rotary Standard Sacenyc

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	8	8	SAND
8	[illegible]	[illegible]	[illegible] + CLAY STREAKS
21	[illegible]	[illegible]	BROWN CLAY
26	[illegible]	[illegible]	GRAVEL + SAND CLAY
37	[illegible]	3	SAND
40	[illegible]	3	GRAVEL + CLAY
[illegible]	[illegible]	[illegible]	CLAY + GRAVEL STREAKS
[illegible]	[illegible]	38	GRAVEL
87	[illegible]	25	GRAVEL + SAND CLAY
112	[illegible]	[illegible]	GRAVEL + SAND
146	166	[illegible]	SAND + GRAVEL
166	170	4	GRAVEL + SAND CLAY
170	178	8	GRAVEL + SAND
178	190	12	SAND + CLAY STREAKS
190	200	10	SAND + LITTLE GRAVEL
200	205	5	SANDY CLAY
205	211	6	SAND + FINE GRAVEL
211	220	9	SAND, GRAVEL + CLAY STREAKS
220	238	13	SAND BOULDERS + FEW CLAY STRAKS
233	241	8	CLAY + GRAVEL
241	255	14	CLAY
255	272	17	CLAY + GRAVEL
272	276	4	CLAY, FEW BOULDERS
276	[illegible]	[illegible]	[illegible]
285	[illegible]	45	CLAY, GRAVEL + SAND [illegible]
330	[illegible]	6	CLAY
336	[illegible]	14	CLAY + GRAVEL [illegible]
350	[illegible]	20	CLAY + GRAVEL STREAKS
370	[illegible]	[illegible]	[illegible]
399	[illegible]	[illegible]	CLAY, GRAVEL + SAND - BROKEN
425	[illegible]	[illegible]	[illegible]

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from ..... to ..... ft.

Other aquifers

First water at ..... feet.

Casing perforated

from ..... to ..... ft.

Size of perforations

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material
428	[illegible]	22	SAND, GRAVEL + CLAY-BROKEN
450	462	12	CLAY
462	470	8	SAND, GRAVEL + CLAY-BROKEN
470	480	10	SANDY CLAY
480	529	49	SAND, GRAVEL + CLAY-BROKEN
529	561	32	GRAVEL + CLAY
561	610	49	CLAY, SANDY WITH LITTLE GRAVEL
610	663	53	SILTSTONE
663	667	4	SAND + GRAVEL
667	680	13	SILTSTONE
680	692	12	SAND, GRAVEL + CLAY-BROKEN
692	721	29	SILTSTONE
721	728	7	SAND + GRAVEL
728	735	7	SILTSTONE
735	[illegible]	5	SAND + GRAVEL

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed.....
Well Driller

By.....

License No.....

Dated....., 19.....

(Not to be filled in by Driller)

LOG 8507

FROM FEET	TO FEET	THICKNESS	
740	776	36	GRAVEL [illegible]
776	781	5	GRAVEL CLAY + SAND (BROWN)
781	782	1	SANDSTONE
782	788	6	GRAVEL + CLAY
788	797	9	SANDSTONE
797	862	65	GRAVEL + CLAY