


# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA



Log No. 8568  
 Rec. June 28 1965  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Do not fill in.

Owner NORMAN D BROWN INC. Driller George Allen

Address Smith Meadows Address Smith Meadows Lic. No. 291

Location of well: NE 1/4  $\frac{1}{4}$  Sec. 20, T. 11N/S, R. 24E, in  Lyon  County  
 or 120 FT N & E MAIN RANCH HOUSE

Water will be used for DOMESTIC Total depth of well 100

Size of drilled hole 6" Weight of casing per linear foot 12

Thickness of casing 3/16" Temp. of water \_\_\_\_\_

Diameter and length of casing 6" - 100'  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure 12 g.p.m.

If nonflowing well give depth of standing water from surface \_\_\_\_\_

If flowing well describe control works 2" valve on side of casing - Well Seal  
(Type and size of valve, etc.) on Pump

Date of commencement of well May 5 1965 Date of completion of well May 10 1965

Type of well rig Hydraulic

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	14	14	GRAVEL
14	24	10	CLAY
24	31	7	GRAVEL + SAND w
31	44	13	SANDY CLAY
44	71	27	CLAY - Blue
71	76	<del>5</del>	Fine GRAVEL w
76	94	18	CLAY - yellow
94	100	6	GRAVEL - w

### Water-bearing Formation, Casing Perforations, etc.

Chief aquifer (water-bearing formation)  
 from 94 to 100 ft.  
 Other aquifers 71 to 76 ft

First water at 24 feet.

Casing perforated  
 from 94 to 100 ft.

Size of perforations  
1/8 x 3 - spht -  
made with Torch

