WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 8882
Rec. Mar 10 19 66
Well No.
Permit No. 20781
Do not fill in.

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Owner: Gerald H. Sharp Driller: Gerald H. Sharp

Address: Nyala via Tonopah, Nevada Address: Lic. No.

Location of well: SW¼ SE¼ Sec. 35, T. 5 N/S, R. 55 E, in Nye County

Permit No. 20781

Water will be used for: irrigation & domestic Total depth of well: 320

Size of drilled hole: 28 inch Weight of casing per linear foot: 50 lbs.

Thickness of casing: 1/4 inch Temp. of water: 60

Diameter and length of casing: 16 inch 320 feet
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure: is not

If nonflowing well give depth of standing water from surface: 76 feet

If flowing well describe control works: not
(Type and size of valve, etc.)

Date of commencement of well: March 14, 1964 Date of completion of well: March 22, 1964

Type of well rig: Winter-Wiess Reverse Circulating Rotary

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	23	23	sandy topsoil
23	29	6	clay
29	32	3	clay & gravel
32	37	5	sand & gravel
37	45	8	clay
45	49	4	sand & gravel
49	59	10	clay, sand & gravel
59	61	12	clay
61	67	6	clay & gravel
67	77	10	clay sand & gravel
77	95	18	sand & gravel
95	108	13	clay & gravel
108	115	7	sand & gravel
115	123	8	clay & sand
123	131	8	sand & gravel
131	144	13	clay & gravel
144	152	8	clay, sand & gravel
152	169	17	sand & gravel
169	174	5	clay sand & gravel
174	188	14	sand & gravel
188	204	6	clay
204	217	13	sand & gravel
217	222	5	clay
222	229	7	clay, sand & gravel
229	240	11	sand & gravel

(OVER)

Water-bearing Formation, Casing Perforations, etc.

Chief aquifer (water-bearing formation)
from 240 to 304 ft.

Other aquifers: 77-95
152-169, 204-217
229-240, 240-304

First water at 76 feet.

Casing perforated
from 160 to 320 ft.

Size of perforations
3/16" x 3"

LOG OF FORMATIONS—Continued

From feet	To feet	Thickness	Type of material
240	251	11	clay, sand & gravel
251	262	11	sand & gravel
262	269	7	clay & sand
269	294	23	sand & gravel
294	301	5	clay & gravel
301	314	13	sand & gravel
314	320	6	clay

CASING RECORD

Diam. casing	From feet	To feet	Length	REMARKS—Seals, Grouting, etc.
16	0	320	320	

GENERAL INFORMATION—Pumping Test, or Boiling Test, Quality of Water, etc.

no test data available

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Gerald H Sharp
Well Driller

By.....

License No.....

Dated March 4, 1966

(Not to be filled in by Driller)

1966 MAR 10 AM 10 56

OHIO
STATE ENGINEER