

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 8888  
 Rec. Mar. 16 1966  
 Well No. \_\_\_\_\_  
 Permit No. 2104E  
*Do not fill in*

Owner Lila May White Driller Charles Nyberg

Address Box 171 Five Points, Calif. Address Box 214 Phelan, Nev. Lic. No. 418

Location of well: 1/4 Sec 12, T. 21 N/S, R. 53 E, in Yuba County  
 or \_\_\_\_\_

Water will be used for irrigation Total depth of well 400'

Size of drilled hole 18" Weight of casing per linear foot 42 lbs

Thickness of casing 1/4" Temp. of water cool

Diameter and length of casing 16" casing 330 feet  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure. \_\_\_\_\_

If nonflowing well give depth of standing water from surface 58'

If flowing well describe control works. \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well May 9, 1965 Date of completion of well Jan 5, 1966

Type of well rig squidder

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	3	3	surface
3	52	49	white clay
52	55	3	caliche
55	62	7	white clay
62	68	6	shale
68	100	32	clay
100	116	16	soft clay
116	118	2	grace
118	122	4	brown clay
122	123	1	shale
123	176	43	soft clay
176	178	2	caliche
178	220	42	brown clay
220	224	4	caliche
224	252	28	brown clay
252	256	4	clay with gravel
256	324	68	soft clay
324	330	6	soft white rock
330	400	70	brown clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)  
 from 324 to 330 ft.

Other aquifers 52-55  
62-68  
220-224

First water at 60 feet.

Casing perforated  
 from 75 to 330 ft.

Size of perforations  
1/2" wide 8" long



