

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA



Log No. 8890
 Rec. Mar 16 1966
 Well No.
 Permit No.

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Do not fill in.

Owner Walker River Paiute Tribe Driller G. Johnson Drilling & Pumps
 Address Schurz Nevada Address Box 60 Tarington Nev. Lic. No. 398
 Location of well N.W. 1/4, T12 N/E R. 31 E, in Mineral County
 or
 Water will be used for Livestock Total depth of well 502 feet
 Size of drilled hole eight inch Weight of casing per linear foot 13.25 lbs
 Thickness of casing .125 Temp. of water normal
 Diameter and length of casing 8-5/8 inch diameter 504 feet long
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
 If flowing well give flow in c.f.s. or g.p.m. and pressure
 If nonflowing well give depth of standing water from surface 458 feet
 If flowing well describe control works
(Type and size of valve, etc.)
 Date of commencement of well 12-6-1965 Date of completion of well 1-14-1966
 Type of well rig cable tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, etc.
0	65	65	mixed clay, sand & rocks	
65	87	22	clay	
87	132	45	mixed clay, sand & hill gravel	Chief aquifer (water-bearing formation)
132	149	17	clay, sand & boulders	from <u>474</u> to <u>502</u> ft.
149	232	83	mixed clay, sand & hill gravel	Other aquifers.....
232	243	11	hard clay	
243	285	42	mixed clay, sand & hill gravel	
285	309	24	loose sand & gravel	
309	389	80	cemented gravel	
389	401	12	rocks	
401	445	44	cemented gravel	
445	451	6	sand	
451	474	23	cemented gravel	First water at <u>445</u> feet.
474	502	28	sand & hill gravel	Casing perforated from <u>472</u> to <u>502</u> ft.

502 1.00 12 11 0 22

1/8 x 4 Size of perforations

