

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY



Log No. 8898
 Rec. Mar 18 1966
 Well No.
 Permit No.
Do not fill in

Owner Tahoe Wood Products Co. Driller Harcin Drilling Company

Address 2051 Hickory St. Carson City, Nevada Address Carson City, Nevada Lic. No. 7988

Location of well: 22 1/4 NW 1/4 Sec. 32, T. 15 N/S, R. 20 E, in Crasby County

Water will be used for Domestic Total depth of well 112 Feet

Size of drilled hole 6" Weight of casing per linear foot 136

Thickness of casing .100 wall Temp. of water Cold

Diameter and length of casing 6" x 112'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure Not Flowing

If nonflowing well give depth of standing water from surface 25 Feet

If flowing well describe control works Not Flowing
(Type and size of valve, etc.)

Date of commencement of well January 15/66 Date of completion of well January 25/66

Type of well rig Cable Tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	40	40	Cemented Sand
40	45	5	Sand
45	70	25	Cemented Sand
70	75	5	Sand
75	85	10	Rock
85	90	5	sand
90	95	5	Cemented Sand
95	105	10	Coarse water sand
105	112	7	Cemented Gravel

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 95 to 105 ft.

Other aquifers 40 To 45

70 To 75

85 To 90

First water at 40 feet.

Casing perforated

from 90 to 112 ft.

Size of perforations

1/8" X 6"

Torch Perforated



