

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 9044
 Rec. July 6 1966
 Well No. _____
 Permit No. 23947
 Do not fill in _____



Owner Dean Orr Driller Loyd Lee Bennett (Lic. No. 416)
(Contractor)
 Address 1141 Ave. H, East Ely, Nev. Address 470 High St. Ely, Nev. Lic. No. 14

Location of well: SW 1/4 NE 1/4 Sec. 22, T6 N, R63 E, in White Pine County
N. 1/2, S. 1/2
 or _____

Water will be used for Office Building, Shops & General
Purposes for new BM location Total depth of well 325'

Size of drilled hole 10" Weight of casing per linear foot 14#

Thickness of casing 5/16" Temp. of water cold

Diameter and length of casing 8" ID 325'
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure _____

If nonflowing well give depth of standing water from surface 155'

If flowing well describe control works _____
 (Type and size of valve, etc.)

Date of commencement of well 5/15/66 Date of completion of well 5/17/66

Type of well rig 24-L BUCYRUS ERIE CABLE TOOL.

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	70'	70'	Gravel & Clay
70'	100'	30'	CLAY
100'	115'	15'	Clay & Sand
115'	120'	5'	Clay
120'	175'	55'	Silt
175'	325'	150'	Sand & Gravel

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 175' to 325' ft.

Other aquifers First water
165'

First water at 165' feet.

Casing perforated

from 165' to 320' ft.

Size of perforations

3/16" x 8", 4 to the
round, every 12".
Forch Perforated.



