WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Basin # 110 A

Log No. 9174
Rec. Sept 22 1966
Well No.
Permit No.

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Do not fill in.

Owner: Harvey Glaizer
Driller: R. N. Powell
Address: Box 117, Schurz, Nevada
Address: R. 2, Box 750 Yerington, Nevada
Lic. No. 272

Location of well: SE 1/4 SE 1/4 Sec. 26, T. 13 N/S, R. 23 E, in Mineral County

or

Water will be used for: Domestic
Total depth of well: 97'

Size of drilled hole: 9 1/2"
Weight of casing per linear foot

Thickness of casing: .156
Temp. of water

Diameter and length of casing: 6 5/8" O.D. - 97'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface: 11'

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well: 8/24/66
Date of completion of well: 8/26/66

Type of well rig: Rotary

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
1	8	8	Sandy clay
8	12	4	Sand
12	14	2	Brown clay
14	26	12	Gray sand
26	28	2	Blue clay
28	42	14	Fine gray sand
42	44	2	Gray clay
44	56	11	Sand - fine to coarse
56	72	16	Gray clay, sandy
72	78	6	Sand and gravel
78	86	8	Sandy clay
86	97	11	Sand and birdseye

Water-bearing Formation, Casing Perforations, etc.

Chief aquifer (water-bearing formation)

from 86 to 97 ft.

Other aquifers: 72 to 78 ft.

First water at 11 feet.

Casing perforated

from 85 to 97 ft.

Size of perforations

3/16" torch cut

(OVER)

LOG OF FORMATIONS—Continued

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	REMARKS—Seals, Grouting, etc.
6 5/8" O.D.	0	97	97'	

GENERAL INFORMATION—Pumping Test, Quality of Water, etc.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed R. M. Lowell
Well Driller

By.....

License No. 272

Dated 9/17/66, 19.....

(Not to be filled in by Driller)