Log No. 9182
Rec. Sep 29 1966
Well No.
Permit No. 20664
Do not fill in.

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Owner Nye County Land Company Driller Roscoe Moss Company

Address La Jolla, California. Address Los Angeles, Calif Lic. No. 8

Location of well NE ¼ NE ¼ Sec. 5, T18 N/S, R 50 E, in Nye County

Permit No. 20664

Water will be used for Irrigation Total depth of well 657

Size of drilled hole 14" Weight of casing per linear foot

Thickness of casing 1/4" wall Temp. of water

Diameter and length of casing 14"
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well July 26, 1966 Date of completion of well August 31, 1966

Type of well rig Calif Type Cable Tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	40	40	Lime and clay
40	45	5	Hard lime
45	70	24	Brown clay
70	105	35	Clay, stks of lime, little pea gravel.
105	130	25	Clay, little lime
130	150	20	Hard brown clay
150	180	30	Grey clay
180	220	40	Grey clay with lime, sandy streaks
220	235	15	Hard lime and gravel
235	260	25	Clay and gravel 4", layers of lime.
260	285	25	Hard lime and stks of sandy clay
285	345	60	Sandy clay, silty grey clay and little gravel
345	405	60	Silty blue clay
405	465	60	Tough brown clay, mixed
465	484	19	Blue and brown clay, mixed
484	645	161	Blue clay, hard stks of of shale
645	657	12	Tough blue clay and silt

Water-bearing Formation, Casing Perforations, etc.

Chief aquifer (water-bearing formation)

from to ft.

Other aquifers

First water at 5 feet.

Casing perforated

from 60 to 530 ft.

Size of perforations
1/2 x 3-1/2

LOG OF FORMATIONS—Continued

From feet	To feet	Thickness	Type of material

RECEIVED
SEP 26 1966
DIV. OF WATER RESOURCES
BRANCH OFFICE
LAS VEGAS, NEVADA

CASING RECORD

Diam. casing	From feet	To feet	Length	REMARKS—Seals, Grouting, etc.
14	0	540		

GENERAL INFORMATION—Pumping Test, or Boiling Test, Quality of Water, etc.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Roscoe Moss Company
Well Driller

By [signature]
Secretary

License No. 8

Dated September 22, 1966

(Not to be filled in by Driller)