Log No. 9185
Rec. Sept 30 1966
Well No.
Permit No.
Do not fill in.

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Owner: EVERETT F. HILL Driller: CLARENCE GORZELL
Address: STAR ROUTE - LAKE CITY, CALIF. Address: LAKE CITY, CALIF. Lic. No. 484
Location of well: SE ¼ SE ¼ Sec. 22, T 45 N/S, R 20 E, in WASHOE County
Permit No.
Water will be used for: LIVESTOCK Total depth of well: 110'
Size of drilled hole: 6 5/8 Weight of casing per linear foot: 13# PER FOOT
Thickness of casing: 3/16" Temp. of water: Cold
Diameter and length of casing: 6 5/8" x 110'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
If flowing well give flow in c.f.s. or g.p.m. and pressure
If nonflowing well give depth of standing water from surface: 17 FEET
If flowing well describe control works
(Type and size of valve, etc.)
Date of commencement of well: SEPT 1/66 Date of completion of well: SEPT 6/66
Type of well rig: CABLE TOOL

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	24	24	Top-soil
24	31	7	CLAY
31	32	1	SAND - COARSE
32	56	24	SAND - CLAY - HARD
56	62	6	SOFT SAND - COARSE
62	97	35	CLAY SAND - HARD
97	110	13	SAND - GRAVEL

(OVER)

Water-bearing Formation, Casing Perforations, etc.

Chief aquifer (water-bearing formation)
from 97' to 110 ft.
Other aquifers
31' - 32'
56' 62'

First water at 31' feet.

Casing perforated
from 50' to 110 ft.

Size of perforations
1/16 x 6"

LOG OF FORMATIONS—Continued

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	REMARKS—Seals, Grouting, etc.
6 5/8	0	110'	110	

GENERAL INFORMATION—Pumping Test, or Boiling Test, Quality of Water, etc.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Clarence Gozell
Well Driller

By

License No. 484

Dated Sept. 11, 19 66

(Not to be filled in by Driller)

1966 SEP 30 AM 11 13