WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 9193
Rec. 10-18 1966
Well No.
Permit No.

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Do not fill in.

Owner Alfredo Trevino Driller Pete Anderson

Address 301 Richards Way, Sparks Nev Address 3590 Churchill Dr. Carson City, Nev. Lic. No. 307

Location of well: ¼ ¼ Sec. 6, T. 6 N/S, R. 20 E, in Washoe County

or Washoe Valley F Arms

Water will be used for Domestic Total depth of well 97'

Size of drilled hole 6" Weight of casing per linear foot 13 lbs.

Thickness of casing 3/16 Temp. of water Cool

Diameter and length of casing 6" 97'

(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 45'

If flowing well describe control works

(Type and size of valve, etc.)

Date of commencement of well Sept 25-66 Date of completion of well Sept-27-66

Type of well rig Cable Tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	10'	10'	Sand
10'	45'	35'	Sandy clay
45	56	11	Course sand
56	63	6	Sandy clay
63	77	14	Fine sand
77	97	20	Course sand & Gravel

1966 OCT 18 AM 10 32

Water-bearing Formation, Casing Perforations, etc.

Chief aquifer (water-bearing formation)

from 77 to 97 ft.

Other aquifers 63-77'

First water at 63 feet.

Casing perforated

from 78 to 97 ft.

Size of perforations

1/8 x 4"

(OVER)

919

LOG OF FORMATIONS—Continued

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	REMARKS—Seals, Grouting, etc.
6"	0	97	97'	All joints electric welded & clay returned to outside of casing

GENERAL INFORMATION—Pumping Test, Quality of Water, etc.

Bailed for 20 minutes. Draw-down 25' at 15 G.P.M.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed [illegible] Well Driller

By .....

License No. 307

Dated Sept 17, 1966

(Not to be filled in by Driller)