WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 9202
Rec. Oct. 21 1966
Well No.
Permit No.
Do not fill in

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Owner: Bureau of Land Management Driller: Effinger Drilling & Pump

Address: Box 1032 Winnemucca, Nevada Address: Box 579 Las Vegas Lic. No. 212

Location of well: ____ ¼ ____ ¼ Sec. 8, T 32 N/S, R 28 E, in Pershing County

or Lava Well

Water will be used for: Stockwater Total depth of well: 430 feet

Size of drilled hole: 10 inch Weight of casing per linear foot: 24.70#

Thickness of casing: .277 Temp. of water:

Diameter and length of casing: 8"ID 400' 6"ID 33'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure:

If nonflowing well give depth of standing water from surface: 330.2 from top of casing.

If flowing well describe control works:
(Type and size of valve, etc.)

Date of commencement of well: October 3, 1966 Date of completion of well: October 10, 1966

Type of well rig: "72 Speedstar"

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	350	350	Decomposed granite, sand, clay
350	430	80	Decomposed granite, sand, clay (Water)

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 350 to 430 ft.

Other aquifers

First water at 350 feet.

Casing perforated
from 350 to 430 ft.

Size of perforations
1/8" X 12" Torch

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
8"ID	0	400	400	Cemented from 0 to 3 feet
6"ID		397	430	Perforated liner in well

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Effinger Drilling & Pump
Well Driller

By A. Effinger

License No. 212

Dated October 19, 19 66

(Not to be filled in by Driller)