WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 9272
Rec. Oct 4 1962
Well No.
Permit No. 20856
Do not fill in

Owner: Chester Osborne Driller: Darell Free

Address: Caliente, Nevada Address: Panaca, Nevada Lic. No. 30

Location of well: N.E. 1/4 S.W. 1/4 Sec. 28, T. 3 N/S, R. 67 E, in Lincoln County

or

Water will be used for: Irrigation Total depth of well: 118

Size of drilled hole: 14" Weight of casing per linear foot

Thickness of casing: 10 gauge Temp. of water

Diameter and length of casing: 14" 120'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure: approx. 100 g.p.m.

If nonflowing well give depth of standing water from surface

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well: September 10, 1962 Date of completion of well: September 19, 1962

Type of well rig: Churn Drill

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	45	45	clay - blue
45	98	53	gravel
98	104	6	cemented gravel
104	118	14	sand and gravel

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 45' to 98 ft.

Other aquifers

First water at 45 feet.

Casing perforated
from 16 to 120 ft.

Size of perforations
1/8 x 1 1/2"

(OVER)

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Well test by Rhodes Brothers Cedar City, Utah
1000 g.p.m. at 40'

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Darell Tree
Well Driller

By

License No. 30

Dated Sept. 23, 1962

OCT 4 AM 9 16
OFFICE STATE ENGINEER

(Not to be filled in by Driller)