Log No. 9288
Rec. Nov. 30 1966
Well No.
Permit No.

Do not fill in.

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Owner: Bureau of Land Management — Driller: C.M. GULLARD DRILLING CO.

Address: Elko District — Address: 6044 S. Euclid Ave. Las Vegas, Nev. — Lic. No. 115

Location of well: NW ¼ NW ¼ Sec. 36, T 34 N/S, R 55 E, in Elko, County

Permit No. (Bid 1930--# 2-Buzzetti--Humboldt Wells)

Water will be used for: Stock wells — Total depth of well: 200 ft.

Size of drilled hole: 8" — Weight of casing per linear foot: 18lbs to foot

Thickness of casing: 280 — Temp. of water:

Diameter and length of casing: 6" 180 ft. plus drive shoe
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure:

If nonflowing well give depth of standing water from surface: 190 ft.

If flowing well describe control works:
(Type and size of valve, etc.)

Date of commencement of well: 11-2-66 — Date of completion of well: 11-10-66

Type of well rig: Cable tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	15	15	Loose gravel
15	20	5	Sandstone
20	160	140	Sandy red clay
160	162	2	Sandstone, gravel, little water
162	200	38	Decomposed rock and bluish gray clay--Water would not rise because of broken structure of ground

1966

Water-bearing Formation, Casing Perforations, etc.

Chief aquifer (water-bearing formation)

from 160 to 162 ft.

Other aquifers

First water at 162 feet.

Casing perforated

from 160 to 180 ft.

Size of perforations

1/4 x 4" 4" centers

919

(OVER)