Log No. 9319
Rec. Dec. 19 1966
Well No.
Permit No.

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Do not fill in.

Owner: Frank Addington Driller: Clarence Gorzell

Address: Cedarville Calif. Box 506 Address: Box 506 Lake City Calif. Lic. No. 484

Location of well: NE ¼ SW ¼ Sec. 14, T. 36 N/S, R. 18 E, in Washoe County

Permit No.

Water will be used for: Stock Total depth of well: 130 FT.

Size of drilled hole: 6" Weight of casing per linear foot: 13 # per foot

Thickness of casing: 3/16" Temp. of water: cold

Diameter and length of casing: 6 5/8" OD - 130'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface: 19 FT.

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well: Nov. 16-1966 Date of completion of well: Nov. 21-1966

Type of well rig: Cable

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	17	17	Top soil
17	37	20	Clay - Sand
37	49	12	Gravel sand - water
49	87	38	Clay sand - hard
87	130	43	Gravel - sand very loose water

Water-bearing Formation, Casing Perforations, etc.

Chief aquifer (water-bearing formation)

from 87 to 130 ft.

Other aquifers 37 - 49

First water at 37 feet.

Casing perforated

from 80 to 130 ft.

Size of perforations

1/8 x 4" Slot

(OVER)

919

LOG OF FORMATIONS—Continued

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	REMARKS—Seals, Grouting, etc.
6 5/8"	0	130	130	

GENERAL INFORMATION—Pumping Test, or Bailing Test, Quality of Water, etc.

Bailing Test 30 G.P.M.

Unable to lower static water level.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Clarence Gorzell
Well Driller

License No. 454

Dated Dec 12, 1966

(Not to be filled in by Driller)