

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 9343
 Rec. Jan 5 1967
 Well No. _____
 Permit No. 23305
 Do not fill in.

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Owner Nye County Land Company Driller Roscoe Moss Company
 Address Lathrop Wells, Nevada Address Los Angeles, Calif. No. 8
 Location of well: SE 1/4 SE 1/4 Sec. 11, T. 18 N/S, R. 50E, in Nye County
 Permit No. 23305
 Water will be used for Irrigation Total depth of well 960
 Size of drilled hole 14 Weight of casing per linear foot 38
 Thickness of casing 1/4" Temp. of water _____
 Diameter and length of casing 14" x 1/4" wall
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
 If flowing well give flow in c.f.s. or g.p.m. and pressure _____
 If nonflowing well give depth of standing water from surface _____
 If flowing well describe control works _____
(Type and size of valve, etc.)
 Date of commencement of well Sept. 1, 1966 Date of completion of well October 14, 1966
 Type of well rig Calif. Cable Tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	2	2	Soil
2	30	28	Soft lime and clay
30	95	65	Hard lime and clay
95	115	20	Hard limestone
115	210	95	Lime and clay (soft)
210	300	90	Clay and lime
300	350	50	Clay and lime
350	375	25	Limestone
375	395	20	Clay and gravel 3"
395	400	5	Clay and gravel 3"
400	530	130	Hard cemented gravel 2"
530	575	45	Hard cemented gravel, clay and little lime 2"
575	690	115	Hard cemented gravel, lime and clay
690	800	110	Hard cemented clay, sand and little gravel
800	805	5	Hard cemented clay and some lime, gravel 1"
805	830	25	Cemented clay, sand and little pea gravel
830	835	5	Cemented gravel 2"
835	880	45	Cemented sand, clay and little pea gravel
880	885	5	Cemented gravel 2"

Water-bearing Formation, Casing Perforations, etc.

Chief aquifer (water-bearing formation)
 from _____ to _____ ft.
 Other aquifers _____

 First water at 7 feet.
 Casing perforated
 from 210 to 840 ft.
 Size of perforations
1/2 x 3-1/4

LOG OF FORMATIONS—Continued

From feet	To feet	Thickness	Type of material
885	900	5	Cemented sand, clay and little pea gravel
900	915	15	Cemented sand, clay and little gravel
915	940	25	Cemented sand and clay
940	960	20	Hard blue clay

CASING RECORD

Diam. casing	From feet	To feet	Length	REMARKS—Seals, Grouting, etc.
14"	0	852		

GENERAL INFORMATION—Pumping Test, or Boiling Test, Quality of Water, etc.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.
 ROSCOE MOSS COMPANY.

Signed.....
Well Driller Secretary

By G. H. [Signature]

License No. 8

Dated December 22, 19 66

(Not to be filled in by Driller)
