WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 9507
Rec. May 25 1967
Well No.
Permit No.
Do not fill in

Owner: Roy Storke
Address: Gardnerville, Nevada
Driller: W. E. Blair
Address: Box 255 Carson City, Lic. No. 301

Location of well: ¼ SW ¼ Sec. 7, T. 12 N/S, R. 20 E, in Douglas County

or

Water will be used for: Stock
Total depth of well: 79 ft
Size of drilled hole: 12" to 32 ft
Weight of casing per linear foot: 12.5 lbs.
Thickness of casing: 11 ga
Temp. of water: cold.
Diameter and length of casing: 8" X 80 ft
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface: 1 ft

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well: 5-1-67
Date of completion of well: 5-4-67

Type of well rig: Cable Tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	5	5	Brown top soil
5	32	27	Brown Sand & Gravel
32	41	9	Blue Sandy Clay
41	44	4	Brown Sand & Gravel
44	79	35	Gray Sand & Gravel

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 56 to 76 ft.

Other aquifers 5-32
41-44

First water at 5 feet.

Casing perforated
from 52 to 76 ft.

Size of perforations
3" X 3/32"

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
8"	0	79	80	Sealed to 32 feet with cement

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Test by ~~Bailing~~ Pump - 100 G.P.M.

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed W. E. Blaw
Well Driller

By Florence Blaw - Co. Owner

License No. 301 48 0

Dated 5 - 11, 1967

(Not to be filled in by Driller)

1967 MAY 25 AM