

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 9539  
Rec. June 15 1967  
Well No. \_\_\_\_\_  
Permit No. 23727  
Do not fill in.

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Owner U.S. Forest Service Driller A & B Contractors  
Intermountain Region 338 Sun Valley Dr.  
Address Ogden, Utah Address Sun Valley, Nev. Lic. No. 287

Location of well: ~~SW~~ <sup>SE</sup> ~~SW~~ <sup>SE</sup> ~~SW~~ <sup>SE</sup> ~~SW~~ <sup>SE</sup> 1/4 Sec. 33, T. 15N, R. 19E, in Ormsby County  
or Clear Creek Conservation Center, Toiyabe National Forest Well # 2

Water will be used for Domestic Total depth of well 251'

Size of drilled hole 16" Weight of casing per linear foot 47 lbs.

Thickness of casing 312 Wall Temp. of water Cold

Diameter and length of casing 16" x 219'  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 125'

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well Nov. 1, 1966 Date of completion of well Dec. 31, 1966  
*FINISHED APRIL 1967*

Type of well rig Cable Tool

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	5	5	Sandy Top Soil
5	94	89	White Granite Sand
94	160	66	Granite Rock Hard
160	187	27	Broken Granite & Sand Water
187	225	38	Hard Granite Rock
225	235	10	Granite Fault or Crevice Water
235	305	70	Hard Granite Rock

This is the log on the test hole. Casing was pulled, then reamed to 240'-- 16"-- Set 8" and bedded in at 251'.

### Water-bearing Formation, Casing Perforations, etc.

Chief aquifer (water-bearing formation)  
from 155 to 187 ft.

Other aquifers 225 to 235'

First water at 155 feet.

Casing perforated  
from 135 to 219 ft.

Size of perforations  
1/4" Mill Slot

