Log No. 9532
Rec. June 15 1967
Well No.
Permit No.
Do not fill in.

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Owner: Steve Wright Driller: O. M. Gullard Drilling Co.

Address: Arthur Route-Wells, Nev. 89835 Address: 6044 S. Euclid, LVN Lic. No. 115

Location of well: SE¼ SE¼ Sec. 2, T. 33 N/~~S~~, R. 60 E, in Elko County

or North Ruby Valley

Water will be used for: Stock well Total depth of well: 150 ft.

Size of drilled hole: 6" Weight of casing per linear foot: 9 lbs

Thickness of casing: 188 Temp. of water:

Diameter and length of casing: 6" 150 ft.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure:

If nonflowing well give depth of standing water from surface: 85 ft.

If flowing well describe control works:
(Type and size of valve, etc.)

Date of commencement of well: 5-22-67 Date of completion of well: 5-26-67

Type of well rig: Cable tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	95	95	Dark gray sandy clay
95	96	1	Sand-1st water
96	125	29	Brown clay
125	127	2	Sandy clay-2nd water
127	145	18	Brown clay
145	150	5	Sand--water

(OVER)

Water-bearing Formation, Casing Perforations, etc.

Chief aquifer (water-bearing formation)

from 145 to 150 ft.

Other aquifers: 125-127

95-96

First water at 96 feet.

Casing perforated

from 105 to 140 ft.

Size of perforations

1/8" x 4"

LOG OF FORMATIONS—Continued

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	REMARKS—Seals, Grouting, etc.
6"	0	150	150	None

GENERAL INFORMATION—Pumping Test, Quality of Water, etc.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed O. M. Gullard Drilling
Well Driller

By O. M. Gullard
O. M. Gullard
License No. 115

Dated June 5, 19 67

(Not to be filled in by Driller)