


# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

293

Log No. \_\_\_\_\_  
 Rec. 7/19 19 54  
 Well No. Denied  
 Permit No. 15713  
*Do not fill in*



Owner Mike Terlizzi Driller S. R. McKinney & Son  
 Address 1100 Comstock Drive Address 1042 South Main In Vel. No. 45  
 Location of well: NW 1/4 NE 1/4 Sec. 6, T. 21 N/S, R. 61 E, in Clark County  
 or \_\_\_\_\_  
 Water will be used for Domestic Total depth of well 150 ft.  
 Size of drilled hole 12" to 50 ft, 10" to 150 ft. Weight of casing per linear foot 10 guage  
 Thickness of casing 10 guage Temp. of water \_\_\_\_\_  
 Diameter and length of casing 8" I.D. to 150 ft.  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_  
 If nonflowing well give depth of standing water from surface 47 ft.  
 If flowing well describe control works \_\_\_\_\_  
 (Type and size of valve, etc.) \_\_\_\_\_  
 Date of commencement of well June 12, 1954 Date of completion of well June 18, 1954  
 Type of well rig 72 Speed Star, Snudder

### LOG OF FORMATIONS

| From feet | To feet | Thickness feet | Type of material      |
|-----------|---------|----------------|-----------------------|
| 0         | 5       | 5              | Surface soil          |
| 5         | 25      | 20             | cemented gravel       |
| 25        | 40      | 15             | loose gravel          |
| 40        | 63      | 23             | cemented gravel       |
| 63        | 72      | 9              | gravelly clay         |
| 72        | 150     | 78             | cemented gravel water |

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 72 to 150 ft.

Other aquifers \_\_\_\_\_

First water at ~~100~~ 68 feet.

Casing perforated

from 60 to 150 ft.

Size of perforations

3/16" X 12"



