WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 9617
Rec. July 26 1967
Well No.
Permit No.
Do not fill in.

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Owner: Industrial Construction Driller: Patrick H. Thompson

Address: Reno, Nevada Address: Las Vegas, Nev. Lic. No. 192

Location of well: SE ¼ NW ¼ Sec. 5, T 16 N/~~S~~, R 20 E, in Washoe County

or

Water will be used for ~~Domestic~~ Construction Total depth of well 200'

Size of drilled hole 0 to 50' 12" - 50 to 200' 10" Weight of casing per linear foot 16.90#

Thickness of casing 3/16" Temp. of water cool

Diameter and length of casing 8 5/8" dia. 180' length
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 69'

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well January 10, 1967 Date of completion of well January 25, 1967

Type of well rig Cable tools

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	30	30	Gravel & sand
30	85	55	Gravel & clay
85	110	25	Sandy clay & gravel
110	116	6	Sand
116	185	69	Brown gritty clay
185	200	15	Blue clay

Water-bearing Formation, Casing Perforations, etc.

Chief aquifer (water-bearing formation)

from to ft.

Other aquifers

First water at 110 feet.

Casing perforated

from 60 95 to 179 120 ft.

Size of perforations 3/16 x 12 4 Rows
1/4 x 3 8 rows on 12" Centers

919

LOG OF FORMATIONS—Continued

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	REMARKS—Seals, Grouting, etc.
8 5/8	plus 1	180	181	Cemented to 50'

GENERAL INFORMATION—Pumping Test, Quality of Water, etc.

Bail tested 80 GPM from 105'

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed [illegible] Well Driller

By [illegible]

License No. 192

Dated 17 March, 19 67

(Not to be filled in by Driller)